# NASA/TM-2000-209891, Vol. 118



# Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall and David E. Knapp, Editors

# Volume 118 BOREAS AES MARSII Surface Meteorological Data

G.B. Atkinson and B. Funk

National Aeronautics and Space Administration

**Goddard Space Flight Center** Greenbelt, Maryland 20771

#### The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and mission, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION.
   English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at http://www.sti.nasa.gov/STI-homepage.html
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:
   NASA Access Help Desk
   NASA Center for AeroSpace Information
   7121 Standard Drive

Hanover, MD 21076-1320

# NASA/TM-2000-209891, Vol. 118



# Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall and David E. Knapp, Editors

# Volume 118 BOREAS AES MARSII Surface Meteorological Data

G. Barrie Atkinson and Barry Funk Environment Canada, Winnipeg, Manitoba, Canada

National Aeronautics and Space Administration

**Goddard Space Flight Center** Greenbelt, Maryland 20771

	Available from:	
NIACA Contourfour Armong units of		Notional Tasks: -1 Informed C
NASA Center for AeroSpace Information		National Technical Information Service
7121 Standard Drive		5285 Port Royal Road
Hanover, MD 21076-1320		Springfield, VA 22161
Drica Codo: A17		Dring Code, A10
Price Code: A17		Price Code: A10

# **BOREAS AES MARSII Surface Meteorological Data**

G. Barrie Atkinson, Barry Funk

# Summary

Canadian AES personnel collected several data sets related to surface and atmospheric meteorological conditions over the BOREAS region. This data set contains 15-minute meteorological data from six MARSII meteorology stations in the BOREAS region in Canada. Parameters include site, time, temperature, dewpoint, visibility, wind speed, wind gust, wind direction, two cloud groups, precipitation, and station pressure. Temporally, the data cover the period of May to September 1994. Geographically, the stations are spread across the provinces of Saskatchewan and Manitoba. The data are provided in tabular ASCII files, and are classified as AFM-Staff data.

#### **Table of Contents**

- 1) Data Set Overview
- 2) Investigator(s)
- 3) Theory of Measurements
- 4) Equipment
- 5) Data Acquisition Methods
- 6) Observations
- 7) Data Description
- 8) Data Organization
- 9) Data Manipulations
- 10) Errors
- 11) Notes
- 12) Application of the Data Set
- 13) Future Modifications and Plans
- 14) Software
- 15) Data Access
- 16) Output Products and Availability
- 17) References
- 18) Glossary of Terms
- 19) List of Acronyms
- 20) Document Information

#### 1. Data Set Overview

#### 1.1 Data Set Identification

BOREAS AES MARSII Surface Meteorological Data

#### 1.2 Data Set Introduction

This data set contains 15-minute meteorological data from six Meteorological Automatic Reporting System II (MARSII) meteorology stations in the BOReal Ecosystem-Atmosphere Study (BOREAS) region in Canada. Parameters include site, time, temperature, dewpoint, visibility, wind speed, wind gust, wind direction, two cloud groups, precipitation, and station pressure. BOREAS received data for the Intensive Field Campaigns (IFCs) of 1994.

#### 1.3 Objective/Purpose

These monitoring sites were established by Environment Canada to provide hourly weather reports to 1) provide input to the operational program of forecasts and warnings, 2) provide input to

operational weather prediction models, and 3) provide climate data. The frequency of observation was increased to 15 minutes at the request of BOREAS. Data collection for BOREAS occurred during IFCs 1, 2, and 3 in 1994.

#### 1.4 Summary of Parameters

Parameters include site, time, temperature, dewpoint, visibility, wind speed, wind gust, wind direction, two cloud groups, precipitation, and station pressure.

#### 1.5 Discussion

Generally, these stations were installed well before BOREAS began, and they conform to Environment Canada's criteria for accuracy and exposure.

#### 1.6 Related Data Sets

BOREAS AFM07 SRC Surface Meteorological Data BOREAS AES Campbell Scientific Surface Meteorological Data BOREAS AES READAC Surface Meteorological Data

## 2. Investigator(s)

#### 2.1 Investigator(s) Name and Title

G. Barrie Atkinson BOREAS AES Project Scientist

#### 2.2 Title of Investigation

Environment Canada 15-Minute MARSII Data

#### 2.3 Contact Information

#### Contact 1:

G. Barrie Atkinson (retired) BOREAS AES Project Scientist Environment Canada 1000 - 266 Graham Avenue Winnipeg, Manitoba Canada R3C 3V4 (204) 983-6059 (204) 983-4884 (fax)

#### Contact 2:

Barry Funk Supervisor, Special Programs Environment Canada 1000 - 266 Graham Avenue Winnipeg, Manitoba Canada R3C 3V4 (204) 983-2018 (204) 984-2072 (fax) Barry.Funk@ec.gc.ca

#### Contact 3:

David Knapp Raytheon ITSS NASA GSFC Code 923 Greenbelt, MD 20771 (301) 286-1424 (301) 286-0239 (fax) David.Knapp@gsfc.nasa.gov

# 3. Theory of Measurements

None given.

# 4. Equipment

# 4.1 Sensor/Instrument Description

Parameter	Instrument	<b>Instrument Description</b>
Pressure	A	Negretti & Zambra aneroid barometer
Cloud	В	Atmospheric and Environment Service (AES) rotating beam ceilometer
	K	AES laser ceilometer Q1211
	L	AES laser ceilometer Q1212
Visibility	C	Sperry videograph, type B
Temperature	D	AES dewcel probe, type E
Radiation shield Precipitation:	E	wooden Stevenson screen, wooden stand
tipping bucket	F	AES tipping bucket rain gauge (TBRG) (summer only)
weighing gauge Wind:	G	Fischer & Porter (F&P) with F&P Nipher shield (winter only)
speed detector	Н	AES/SD-B, MARS II type U2A
direction detector	I	AES/DD-C, MARS II type U2A
Tower	J	Hossick tilting

#### 4.1.1 Collection Environment

The instrumentation was operated at ambient environmental conditions during the data period.

#### 4.1.2 Source/Platform

The following table lists the instrumentation at the various MARSII stations by the codes given in Section 4.1.

			Statio	ns		
Instrument	WEQ	WDC	WJD	WOY	WSZ	WVT
Pressure sensor	A	A	A	A	A	A
Cloud sensor	В	K	-	L	В	K
Visibility sensor	C	-	C	C	C	C
Temperature/dewpoint sensor	D	D	D	D	D	D
height (cm)	116	112	120	120	118	120
radiation shield	E	E	E	E	E	E
Precipitation:						
Tipping Bucket	F	F	F	F	F	F
rim height (cm)	75	75	75	75	75	75
Weighing gauge	G	-	-	G	-	-
rim height (cm)	230	-	-	201	-	-
Anemometer:						
speed sensor	Н	Н	Н	Н	Н	Н
cup height (m)	10	10	16	10	10	10
direction sensor	I	I	I	I	I	I
Tower	J	J	J	J	J	J

## 4.1.3 Source/Platform Mission Objectives

None given.

#### 4.1.4 Key Variables

The key variables in these data are: site, time, temperature, dewpoint, visibility, wind speed, wind gust, wind direction, two cloud groups, precipitation, and station pressure.

#### 4.1.5 Principles of Operation

None given.

#### 4.1.6 Sensor/Instrument Measurement Geometry

None given.

#### 4.1.7 Manufacturer of Sensor/Instrument

None given.

#### 4.2 Calibration

#### 4.2.1 Specifications

None given.

#### **4.2.1.1 Tolerance**

None given.

#### 4.2.2 Frequency of Calibration

None given.

#### 4.2.3 Other Calibration Information

None given.

# **5. Data Acquisition Methods**

Since there is no provision for onboard storage of observations, each station was telephoned approximately every 15 minutes from a computer in Winnipeg.

# 6. Observations

#### 6.1 Data Notes

Not applicable.

#### **6.2 Field Notes**

The following was obtained from the inspection books. Obviously some visits have not been recorded. Normal practice is to disable the TBRG for the winter and to disable the weighing gauge for the summer.

Location	Date of Visit	Actions During Visit
WEQ Swan River, MB	Inspection 21-Mar-1994	All instruments were cleaned and calibrated. Pressure averaged +0.235 mb different from the inspection barometer for 10 readings. Clouds were too high and too few to verify operation of the ceilometer. Temperature averaged 0.0 °C different from inspection psychrometer for 9 readings. The dewpoint was +1.2 deg °C different. A newly calibrated tipping bucket bridge was installed and checked. Bearings in both the speed and direction wind detectors were replaced.
	Visit 18-May-1995	F&P taken out of service and TBRG installed for the summer.
WDC Uranium City, SK	Inspection 06-Dec-1993	All instruments were cleaned and calibrated. Pressure averaged -0.42 mb different from the inspection barometer for 10 readings. The wind speed detector and the dewcel were changed as per their replacement schedule. The wind direction indicator was still in good condition.
WJD Grand Rapids, MB	Inspection 20-Apr-1993	All instruments were cleaned and calibrated. Pressure averaged -0.55 mb different from the inspection barometer. Air temperatures were within +/- 0.2 °C, and dewpoint temperatures were within +/- 0.7 degrees °C.
	Inspection 22-Jul-1994	All instruments were cleaned and calibrated. Pressure averaged +0.654 mb different from the inspection barometer.
	Inspection 29-Mar-1995	All instruments were cleaned and calibrated. Pressure averaged +0.71 mb different from the inspection barometer for six comparisons. The dewpoint was reading higher than temperature. The problem was traced to an out-of-alignment temperature bridge card, which was replaced with a spare. Then psychrometer/MARS II comparisons were well within limits.
	Visit 24-May-1995	TBRG installed for the summer.

WOY Wynard, SK	Inspection 20-Jul-1994	All instruments were cleaned and calibrated. The dewcel was changed. The amplifier in the videograph was replaced, and the videograph is now back in service.
	Inspection 24-Nov-1994	All instruments were cleaned and calibrated. The dewcel was changed. The aneroid barometer was replaced. The nipher shield was placed on the F&P, and it is now in service. The TBRG was removed for the winter.
WSZ Fisher Branch, MB	Inspection 17-Mar-1993	All instruments were cleaned and calibrated. Pressure averaged -0.25 mb different from the inspection barometer for 10 comparisons. Temperature comparisons were within 0.2 degrees C and the dewpoint was within 1.0 degrees C.
	Visit 21-Apr-1995	The TBRG was installed for the summer.
WVT Buffalo Narrows SK	Inspection 20-Jul-1992	All instruments were cleaned and calibrated. Temperature comparisons were on average -0.2 degrees C and the dewpoint was on average +0.2 degrees C. Wind speed detector was replaced.
	Inspection 12-Aug-1994	All instruments were cleaned and calibrated, and found to be within limits. Wind speed detector was replaced. TBRG was leveled.
	Visit 22-Nov-1994	Wind system was malfunctioning. Wind speed detector was replaced. TBRG was taken out of service for the winter.
	Inspection 12-Dec-1994	All instruments were cleaned and calibrated, and found to be within limits.

# 7. Data Description

# 7.1 Spatial Characteristics

#### 7.1.1 Spatial Coverage

The following is a list of stations covered by the data. Latitude and longitude are given in degrees and minutes under the North American Datum of 1983 (NAD83). A brief description of each station follows.

ID	Name	Latitude	Longitude	Elevation (meters)
WEQ	Swan River, MB	52° 07' N	101° 14' W	334.8
WDC	Uranium City, SK	59° 34' N	108° 29' W	318.2
WJD	Grand Rapids, MB	53° 11' N	99° 16' W	222.5
WOY	Wynard, SK	51° 46' N	104° 12' W	560.1
WSZ	Fisher Branch, MB	51° 05' N	97° 33' W	253.0
WVT	Buffalo Narrows, SK	55° 50' N	108° 26' W	434.0

#### WEQ Swan River, MB

The autostation is located at the Swan River Airport in the Swan River Valley. Exposure is open in all directions. Instruments are located on a level, grassed surface. The Valley runs in a southwest to northeast direction with the Porcupine Mountains to the north-northwest and the Duck Mountains to the south-southeast. The Valley bottom is fairly flat cropland with the occasional bluff of trees.

#### WDC Uranium City, SK

The instrument area is located on a 23-m-wide strip of grass running northeast from the airport terminal building. This grassy area is sandwiched between a gravel vehicle parking area to the southeast and a paved aircraft parking ramp to the northwest. The instrument exposure is fair, with some sheltering to the northeast by the Eldorado warehouse and to the west by the air terminal building. Airflow from the north and south is generally unrestricted, although the south side of the instrument area is bounded by a 2-m security fence. The instruments are subject to occasional "propwash" from aircraft in the parking area immediately to the north. The airport is located approximately 15 km to the north of Lake Athabaska, and the surrounding countryside is quite hilly, and covered with evergreen and birch trees. Numerous small lakes dot the area.

#### WJD Grand Rapids, MB

The site is located in the town of Grand Rapids, just north of the intersection of the main thoroughfare of the town and Highway #6. Instrument exposure is very good. Instruments are located in a 30-m-square area surrounded by a 1.2-m-high chain link fence. Low brush has been cleared to a distance of approximately 60 m in all directions. The surrounding terrain is flat, with mixed forest, scrub bush, and muskeg. The mouth of the Saskatchewan River, where it flows into the north basin of Lake Winnipeg, is approximately 1 km to the southeast. These two bodies of water, particularly open water on faster flowing sections of the river, contribute to high year-round humidities, frequent fog conditions, and heavy hoarfrost in the winter months. The wind exposure is excellent in all directions because the 16-m wind mast extends well above the surrounding treetops. In addition, the nearest tall trees (5-10 m) are at least 70 m away.

#### WOY Wynard, SK

The autostation is located at 505 5th St. W, at the corner of 5th St and Highway #16, in the southwest corner of the town of Wynard (population approximately 2200). The station is situated on a parcel of land that is approximately 98 m (north-south) by 152 m (east-west), grassed, and surrounded by a fence. Buildings from the former manned program are at the west end of the property, and the instruments are located in a 30-m by 30-m plot near the center of the property, with the wind tower near the east end. The immediate surroundings are: North - residential street, mostly one-story single family dwellings; East - open school yard; South - Provincial Highway #16; and West - the local golf course. Farther out to the north and east are residential and business districts. Farther to the south and west is mostly open crop and pasture land. The Quill lakes are located to the west and northwest, with the closest shoreline approximately 8 km away. These lakes are very shallow and can produce local low clouds during periods of northwest winds. The local terrain is mostly gently rolling farmland, open except for an occasional farm shelterbelt or small wooded area in a depression. The topography has a gentle slope from the Touchwood Hills (elevation 670 m) some 10 km to the south, to the shores of the Quill lakes to the northwest (elevation 533 m). The site offers an excellent exposure from all directions and is representative of the area.

#### WSZ Fisher Branch, MB

The station is situated at the southeast end of the 240-m (north-south) by 90-m (east-west) AES reserve. The instrument area is a 25-m-square grass on gravel area in a rural setting and has good exposure. The reserve has been cleared of trees, but a line of trees borders the reserve on the western and northern edges. The surrounding countryside is generally flat farmland, with about 30% tree coverage. Lake Winnipeg lies about 50 km to the east and Lake Manitoba about 70 km to the west.

#### WVT Buffalo Narrows, SK

The autostation instruments are colocated with the manned site on a large (60 by 60 m) grass-covered area surrounded by a wire security fence situated along the southwest side of the Buffalo Narrows airport. The airport is located on a broad peninsula that extends northeastward into Churchill Lake. Topography within a 30-km radius is 50% thickly treed bush and muskeg, and 50% large and small lakes of the Churchill River system. The wind tower is located near the runway, with open exposure in all directions.

#### 7.1.2 Spatial Coverage Map

Not available.

#### 7.1.3 Spatial Resolution

These data represent point measurements at the given locations.

#### 7.1.4 Projection

Not applicable.

#### 7.1.5 Grid Description

Not applicable.

#### 7.2 Temporal Characteristics

#### 7.2.1 Temporal Coverage

Data were collected at the sites from 24-May-1994 through 25-Jun-1994, from 18-Jul-1994 through 18-Aug-1994, and from 25-Aug-1994 through 20-Sep-1994.

#### 7.2.2 Temporal Coverage Map

Not available.

#### 7.2.3 Temporal Resolution

Data are reported approximately every 15-minutes.

#### 7.3 Data Characteristics

#### 7.3.1 Parameter/Variable

Column Name

The parameters contained in the data files on the CD-ROM are:

SITE\_NAME SUB SITE DATE\_OBS TIME OBS AIR TEMP 1 5M DEW\_TEMP\_1\_5M MEAN WIND SPEED 10M 10MIN VISIBILITY\_INDEX GUST\_10M\_10MIN MEAN\_WIND\_DIR\_10M\_10MIN CLOUD GROUP 1 CLOUD\_GROUP\_2 ACCUM\_PRECIP\_TIP STN\_PRESS CRTFCN\_CODE REVISION DATE

**7.3.2 Variable Description/Definition**The descriptions of the parameters contained in the data files on the CD-ROM are:

Column Name	Description
SITE_NAME	The identifier assigned to the site by BOREAS, in the format SSS-TTT-CCCCC, where SSS identifies the portion of the study area: NSA, SSA, REG, TRN, and TTT identifies the cover type for the site, 999 if unknown, and CCCCC is the identifier for site, exactly what it means will vary with site type.
SUB_SITE	The identifier assigned to the sub-site by BOREAS, in the format GGGGG-IIIII, where GGGGG is the group associated with the sub-site instrument, e.g. HYD06 or STAFF, and IIIII is the identifier for sub-site, often this will refer to an instrument.
DATE_OBS	The date on which the data were collected.
TIME_OBS	The Greenwich Mean Time (GMT) when the data were collected.
AIR_TEMP_1_5M	The instantaneous air temperature at a height of 1.5 meters above the surface.
DEW_TEMP_1_5M	The instantaneous dewpoint temperature at a height of 1.5 meters above the surface.
MEAN_WIND_SPEED_10M_10MIN	The ten minute mean wind speed at a height of ten meters above the surface.
VISIBILITY_INDEX	The visibility index. This value is a number that can be converted to an approximate visibility in nautical miles. The following table can be used to do this conversion.

Actual Visibility	Ranges of Values	in Data
(nautical miles)	WITH PRECIPITATION	NO PRECIPITATION
9.+	961-999 & 0-96	961-999 & 0-96
8.	97-110	97-110
7.	111-125	111-125
6.	126-144	126-144
5.	145-166	145-166
4.5	167-178	167-178
4.	179-193	179-193
3.5	194-209	194-209
3.	210-229	210-229
2.5	230-246	230-252
2.	247-264	253-282
1.8	265-272	283-296
1.6	273-282	297-312
1.4	283-293	313-330
1.2	294-305	331-352
1.0	306-319	353-378
0.9	320-328	379-393
0.8	329-337	394-411
0.7	338-348	412-431
0.6	349-360	432-455

0.5	361-375	456-484
0.4	376-393	485-521
0.3	394-416	522-570
0.2	417-448	571-645
0.1	449-504	646-794
0.0	505-960	795-960

Note: The "NO PRECIPITATION" values are used only when there is explicit input from the TBRG to indicate that NO precipitation has fallen. e.g. during the winter or at any other time when the precipitation sensor has been removed from the station configuration, use the "WITH PRECIPITATION" column.

GUST\_10M\_10MIN

MEAN\_WIND\_DIR\_10M\_10MIN

CLOUD\_GROUP\_1

The maximum wind speed over the past ten minutes at a height of ten meters above the surface. The ten minute mean wind direction at a height of ten meters above the surface. The first two digits denote the height of the last detected cloud in hundreds of feet within the last six minutes. The next digit can be a 1 if cloud is overhead at the time of observation, or a 0 if no cloud. The last digit denotes the percentage of time, in tens of percent, that clouds were detected overhead during the previous hour.

ChChCwC% (Field is 4 numbers long)

ChCh Height of last detected cloud (100s feet) within the last 6 minutes

- Cw 1 = cloud overhead at time of observation;
  0 = no cloud
- C% 10s percent of time cloud detected overhead during previous hour

CLOUD\_GROUP\_2

The first digit is for the 0 to 500 feet layer (0 to 174 meters), the second is for the 501 to 1000 feet layer (174 to 348 meters), the third is for the 1001 to 2000 feet layer (348 to 610 meters), and the fourth is for above 2001 feet (610 meters). A 0 in any place (layer) denotes no cloud in that layer in the last fifty minutes or more, a 1 denotes no cloud in the past forty minutes or more, a 2 denotes no cloud in the past thirty minutes or more, a 3 denotes no cloud in the past twenty minutes or more, a 4 denotes no cloud in the past ten minutes or more, a 5 means that cloud became either significant or insignificant within the last ten minutes, a 6 denotes cloud detected for the past ten minutes or more, a 7 denotes cloud detected for the past twenty minutes or more, a 8 denotes cloud detected for the past thirty minutes or more, a 9

denotes cloud detected for the past forty minutes or more.

C1C2C3C4 (Field is 4 numbers long)

C1		0	- 500	fee	et					
C2	5	01	- 1000	) fe	eet					
C3	10	01	- 2000	) fe	eet					
C4	abo	ove	2001	. fe	eet					
NUMBE	RS	an	y numk	er	can	appea	ar :	in any he	eigł	nt
0	- 1	no	cloud	in	the	past	50	minutes	or	more
1	- 1	no	cloud	in	the	past	40	minutes	or	more
2	- 1	no	cloud	in	the	past	30	minutes	or	more
3	- 1	no	cloud	in	the	past	20	minutes	or	more
4	- 1	no	cloud	in	the	past	10	minutes	or	more

5 - transition - cloud became significant or insignificant in the last 10 minutes

 cloud detected for the past 10 minutes or more

7 - cloud detected for the past 20 minutes or more

8 - cloud detected for the past 30 minutes or more

9 - cloud detected for the past 40 minutes or more

ACCUM\_PRECIP\_TIP The amount of liquid precipitation that has

HEIGHTS

fallen since a relative date.

STN\_PRESS The measured instantaneous atmospheric pressure

at station level.

CRTFCN\_CODE The BOREAS certification level of the data.

Examples are CPI (Checked by PI), CGR (Certified

by Group), PRE (Preliminary), and CPI-???

(CPI but questionable).

REVISION\_DATE The most recent date when the information in the referenced data base table record was revised.

#### 7.3.3 Unit of Measurement

The measurement units for the parameters contained in the data files on the CD-ROM are:

Column Name	Units
SITE_NAME	[none]
SUB_SITE	[none]
DATE_OBS	[DD-MON-YY]
TIME_OBS	[HHMM GMT]
AIR_TEMP_1_5M	[degrees Celsius]
DEW_TEMP_1_5M	[degrees Celsius]
MEAN_WIND_SPEED_10M_10MIN	[meters][second^-1]
VISIBILITY_INDEX	[none]
GUST_10M_10MIN	[meters][second^-1]
MEAN_WIND_DIR_10M_10MIN	[degrees true North]

CLOUD_GROUP_1	[none]
CLOUD_GROUP_2	[none]
ACCUM_PRECIP_TIP	[millimeters]
STN_PRESS	[kiloPascals]
CRTFCN_CODE	[none]
REVISION DATE	[DD-MON-YY]

# 7.3.4 Data Source

The sources of the parameter values contained in the data files on the CD-ROM are:

Column Name	Data Source
SITE_NAME	[Assigned by BORIS]
SUB_SITE	[Assigned by BORIS]
DATE_OBS	[Supplied by Investigator]
TIME_OBS	[Supplied by Investigator]
AIR_TEMP_1_5M	[Supplied by Investigator]
DEW_TEMP_1_5M	[Supplied by Investigator]
MEAN_WIND_SPEED_10M_10MIN	[Supplied by Investigator]
VISIBILITY_INDEX	[Supplied by Investigator]
GUST_10M_10MIN	[Supplied by Investigator]
MEAN_WIND_DIR_10M_10MIN	[Supplied by Investigator]
CLOUD_GROUP_1	[Supplied by Investigator]
CLOUD_GROUP_2	[Supplied by Investigator]
ACCUM_PRECIP_TIP	[Supplied by Investigator]
STN_PRESS	[Supplied by Investigator]
CRTFCN_CODE	[Assigned by BORIS]
REVISION_DATE	[Assigned by BORIS]

## 7.3.5 Data Range

The following table gives information about the parameter values found in the data files on the CD-ROM.

	Minimum	Maximum	Missng	Unrel	Below	Data
	Data	Data	Data	Data	Detect	Not
Column Name	Value	Value	Value	Value		Cllctd
SITE_NAME	REG-999-WDC04	REG-999-WVT04	None	None	None	None
SUB_SITE	STAFF-AES04	STAFF-AES04	None	None	None	None
DATE_OBS	24-MAY-94	20-SEP-94	None	None	None	None
TIME_OBS	0	2359	None	None	None	None
AIR_TEMP_1_5M	0	40.8	None	None	None	None
DEW_TEMP_1_5M	1	52	None	None	None	None
MEAN_WIND_SPEED_10M_	0	51.286	-999	None	None	None
10MIN						
VISIBILITY_INDEX	0	999	None	None	None	None
GUST_10M_10MIN	0	51.286	-999	None	None	None
MEAN_WIND_DIR_10M_	0	359	None	None	None	None
10MIN						
CLOUD_GROUP_1	0000	S000	-999	None	None	None
CLOUD_GROUP_2	0000	Z000	-999	None	None	None
ACCUM_PRECIP_TIP	0	1960.6	None	None	None	None
STN_PRESS	9.82	100.05	-999	None	None	None
CRTFCN_CODE	CPI	CPI	None	None	None	None

REVISION_DATE	19-DEC-95	22-JUN-98	None	None	None	None
Minimum Data Value Maximum Data Value Missng Data Value	the colur dissing dat as made to	mn. ta. This o determ	nine the	l to		
Unrel Data Value	The value the to indicate parameter va	alue, but the a nat indicates u an attempt was alue, but the v by the analysis	nreliable made to dalled	data. determir deemed t	This is ne the	used
Below Detect Limit	instruments indicate that parameter vathat the par	nat indicates p detection limi at an attempt w alue, but the a rameter value w instrumentati	ts. This as made to nalysis pe as below t	is used o determ ersonnel	l to nine the . determi	
Data Not Cllctd	indicates th not identica	ne parameter va nat BORIS combi al data sets in cticular scienc	lue. This ned severa to the sar	s usuall al simil me data	y .ar but	ole
Blank Indicates N/A Indicates None Indicates	that the value	is not applica	ble to the	e respec	tive col	

#### 7.4 Sample Data Record

The following are wrapped versions of data record from a sample data file on the CD-ROM.

```
SITE_NAME, SUB_SITE, DATE_OBS, TIME_OBS, AIR_TEMP_1_5M, DEW_TEMP_1_5M, MEAN_WIND_SPEED_10M_10MIN, VISIBILITY_INDEX, GUST_10M_10MIN, MEAN_WIND_DIR_10M_10MIN, CLOUD_GROUP_1, CLOUD_GROUP_2, ACCUM_PRECIP_TIP, STN_PRESS, CRTFCN_CODE, REVISION_DATE
'REG-999-WSZ04', 'STAFF-AES04',01-JUN-94,2,19.6,5.4,5.756,8,8.479,329,'0000', '0000',21.2,98.72,'CPI',19-DEC-95
'REG-999-WSZ04', 'STAFF-AES04',01-JUN-94,17,20.0,6.6,4.676,8,7.349,328,'0000', '0000',21.2,98.72,'CPI',19-DEC-95
```

# 8. Data Organization

#### 8.1 Data Granularity

The smallest unit of data is a monthly set of 15-minute records for one station.

#### 8.2 Data Format(s)

The Compact Disk-Read-Only Memory (CD-ROM) files contain American Standard Code for Information Interchange (ASCII) numerical and character fields of varying length separated by commas. The character fields are enclosed with single apostrophe marks. There are no spaces between the fields.

Each data file on the CD-ROM has four header lines of Hyper-Text Markup Language (HTML)

code at the top. When viewed with a Web browser, this code displays header information (data set title, location, date, acknowledgments, etc.) and a series of HTML links to associated data files and related data sets. Line 5 of each data file is a list of the column names, and line 6 and following lines contain the actual data.

# 9. Data Manipulations

#### 9.1 Formulae

None given.

#### 9.1.1 Derivation Techniques and Algorithms

Not applicable.

#### 9.2 Data Processing Sequence

#### 9.2.1 Processing Steps

Data were received by BOREAS in raw form with 1 month's worth of data per station contained in each raw file. They were extracted from the files using a C program provided by AES. The output of this program was a tab-delimited file that contained 1 month's worth of processed data for one station. BOREAS Information System (BORIS) personnel loaded these data into a relational data base and converted the units as needed to match those of other data sets.

#### 9.2.2 Processing Changes

'RAW' data had many extraneous characters that were removed. The records were checked for completeness.

#### 9.3 Calculations

No calculations were performed on the data.

#### 9.3.1 Special Corrections/Adjustments

None given.

#### 9.3.2 Calculated Variables

None given.

#### 9.4 Graphs and Plots

None given.

#### 10. Errors

#### 10.1 Sources of Error

Snow measurements (Fisher) are known to be poor.

#### 10.2 Quality Assessment

#### 10.2.1 Data Validation by Source

None given.

#### 10.2.2 Confidence Level/Accuracy Judgment

None given.

#### **10.2.3 Measurement Error for Parameters**

None given.

#### 10.2.4 Additional Quality Assessments

None given.

#### 10.2.5 Data Verification by Data Center

An automated quality assurance program was run on this data set to identify anomalies, including sudden jumps or drops ("spikes") in the data. Some of these problems are identified in Section 11.2.

#### 11. Notes

#### 11.1 Limitations of the Data

None given.

#### 11.2 Known Problems with the Data

#### AIR\_TEMP\_1\_5\_M

			From	То	
Prob	SITE_NAME	SUB_SITE	DATE_OBS	DATE_OBS	Data
	· 	· 			
Spike	REG-999-WOY04	STAFF-AES04	05-JUN-94	05-JUN-94	20.5 - 40.8
Spike	REG-999-WOY04	STAFF-AES04	05-JUN-94	05-JUN-94	40.8 - 18

#### DEW\_TEMP\_1\_5\_M

Some large spikes were identified for these data at the WDC and WVT sites.

These high values are most likely not valid.

Spike	REG-999-WDC04	STAFF-AES04	05-AUG-94	06-AUG-94	17.2 - 52
Spike	REG-999-WDC04	STAFF-AES04	06-AUG-94	06-AUG-94	52 - 17.1
High	REG-999-WDC04	STAFF-AES04	06-AUG-94	06-AUG-94	52
Spike	REG-999-WVT04	STAFF-AES04	22-JUL-94	22-JUL-94	26.1 - 9.8
C 1	i contract of the contract of				
Spike	REG-999-WVT04	STAFF-AES04	30-JUL-94	30-JUL-94	15.2 - 51.3
Spike Spike	REG-999-WVT04  REG-999-WVT04	1	1	30-JUL-94    30-JUL-94	15.2 - 51.3 51.3 - 22.6

#### MEAN\_WIND\_SPEED\_10M\_10MIN

There was an intermittent problem from May 1994 to September 1994 at WEQ. The values greater than 51 are probably not valid.

```
Spike | REG-999-WEQ04 | STAFF-AES04 | 27-MAY-94 | 27-MAY-94 | 51.286 - .668
High | REG-999-WEQ04 | STAFF-AES04 | 27-MAY-94 | 27-MAY-94 | 51.286
```

There was an intermittent problem from 31-Aug-1994 to 04-Sep-1994 at WVT.

Spike	REG-999-WVT04	STAFF-AES04	31-AUG-94	31-AUG-94	0 - 51.235
High	REG-999-WVT04	STAFF-AES04	31-AUG-94	31-AUG-94	51.235
Spike	REG-999-WVT04	STAFF-AES04	31-AUG-94	31-AUG-94	51.183 - 1.285
High	REG-999-WVT04	STAFF-AES04	31-AUG-94	31-AUG-94	51.183

#### VISIBILITY INDEX

This column contains many spikes. One example of this is listed below. Users should be cautious about using this parameter. See Section 7.3.2 for more information.

```
Spike | REG-999-WSZ04 | STAFF-AES04 | 20-SEP-94 | 20-SEP-94 | 994 - 5
```

#### GUST\_10M\_10MIN

A number of spikes were found at the WEQ site that appear to be related to the wind speed spikes at this site. Similar spikes were found at the WJD and WVT sites.

```
Spike | REG-999-WEQ04 | STAFF-AES04 | 02-SEP-94 | 02-SEP-94 | 51.286 - .617
High | REG-999-WEQ04 | STAFF-AES04 | 02-SEP-94 | 02-SEP-94 | 51.286
```

#### MEAN WIND DIR 10M 10MIN

No serious problems were found with these data.

#### ACCUM PRECIP TIP

Extremely large values greater than 1900 were found for the WEQ and WVT sites.

```
Spike | REG-999-WEQ04 | STAFF-AES04 | 03-AUG-94 | 03-AUG-94 | 1944.6 - 17.8 | High | REG-999-WEQ04 | STAFF-AES04 | 03-AUG-94 | 03-AUG-94 | 1944.6 | Spike | REG-999-WVT04 | STAFF-AES04 | 21-JUN-94 | 21-JUN-94 | 106.4 - 1927.2 | Spike | REG-999-WVT04 | STAFF-AES04 | 21-JUN-94 | 21-JUN-94 | 1927.2 - 106.4
```

#### STN PRESS

Extremely low values were seen in the data for the WDC and WVT sites.

```
Spike | REG-999-WDC04 | STAFF-AES04 | 03-AUG-94 | 03-AUG-94 | 9.87 - 98.74 | Low | REG-999-WDC04 | STAFF-AES04 | 03-AUG-94 | 03-AUG-94 | 9.87
```

The original data appears to have a missing digit. The 9.87 value should probably be 98.70.

```
Spike | REG-999-WVT04 | STAFF-AES04 | 17-JUN-94 | 17-JUN-94 | 26.96 - 96.95
Low | REG-999-WVT04 | STAFF-AES04 | 17-JUN-94 | 17-JUN-94 | 26.96
```

It is assumed that the value of 26.96 should really be 96.96.

#### 11.3 Usage Guidance

None given.

#### 11.4 Other Relevant Information

None given.

# 12. Application of the Data Set

These data in conjunction with other surface meteorological data can be used to monitor and model the near-surface conditions on a diurnal and seasonal basis.

#### 13. Future Modifications and Plans

None given.

#### 14. Software

#### 14.1 Software Description

A C program from AES was used for unpacking and converting RAW data files.

#### 14.2 Software Access

#### **Contact:**

Barry Funk Supervisor, Special Programs Environment Canada 1000 - 266 Graham Avenue Winnipeg, Manitoba Canada R3C 3V4 (204) 983-2018 (204) 984-2072 (fax) Barry.Funk@ec.gc.ca

#### 15. Data Access

The AES MARSII surface meteorological data are available from the Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC).

#### **15.1 Contact Information**

For BOREAS data and documentation please contact:

ORNL DAAC User Services Oak Ridge National Laboratory P.O. Box 2008 MS-6407 Oak Ridge, TN 37831-6407 Phone: (423) 241-3952

Fax: (423) 574-4665

E-mail: ornldaac@ornl.gov or ornl@eos.nasa.gov

#### 15.2 Data Center Identification

Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC) for Biogeochemical Dynamics http://www-eosdis.ornl.gov/ [Internet Link].

#### 15.3 Procedures for Obtaining Data

Users may obtain data directly through the ORNL DAAC online search and order system [http://www-eosdis.ornl.gov/] and the anonymous FTP site [ftp://www-eosdis.ornl.gov/data/] or by contacting User Services by electronic mail, telephone, fax, letter, or personal visit using the contact information in Section 15.1.

#### 15.4 Data Center Status/Plans

The ORNL DAAC is the primary source for BOREAS field measurement, image, GIS, and hardcopy data products. The BOREAS CD-ROM and data referenced or listed in inventories on the CD-ROM are available from the ORNL DAAC.

# 16. Output Products and Availability

#### **16.1 Tape Products**

None.

#### 16.2 Film Products

None.

#### 16.3 Other Products

These data are available on the BOREAS CD-ROM series.

#### 17. References

# 17.1 Platform/Sensor/Instrument/Data Processing Documentation

None given.

#### 17.2 Journal Articles and Study Reports

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. 2000. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM.

Sellers, P. and F. Hall. 1994. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1994-3.0, NASA BOREAS Report (EXPLAN 94).

Sellers, P. and F. Hall. 1996. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1996-2.0, NASA BOREAS Report (EXPLAN 96).

Sellers, P., F. Hall, and K.F. Huemmrich. 1996. Boreal Ecosystem-Atmosphere Study: 1994 Operations. NASA BOREAS Report (OPS DOC 94).

Sellers, P., F. Hall, and K.F. Huemmrich. 1997. Boreal Ecosystem-Atmosphere Study: 1996 Operations. NASA BOREAS Report (OPS DOC 96).

Sellers, P., F. Hall, H. Margolis, B. Kelly, D. Baldocchi, G. den Hartog, J. Cihlar, M.G. Ryan, B. Goodison, P. Crill, K.J. Ranson, D. Lettenmaier, and D.E. Wickland. 1995. The boreal ecosystem-atmosphere study (BOREAS): an overview and early results from the 1994 field year. Bulletin of the American Meteorological Society. 76(9):1549-1577.

Sellers, P.J., F.G. Hall, R.D. Kelly, A. Black, D. Baldocchi, J. Berry, M. Ryan, K.J. Ranson, P.M. Crill, D.P. Lettenmaier, H. Margolis, J. Cihlar, J. Newcomer, D. Fitzjarrald, P.G. Jarvis, S.T. Gower, D. Halliwell, D. Williams, B. Goodison, D.E. Wickland, and F.E. Guertin. 1997. BOREAS in 1997: Experiment Overview, Scientific Results and Future Directions. Journal of Geophysical Research 102(D24): 28,731-28,770.

# 17.3 Archive/DBMS Usage Documentation

None.

#### 18. Glossary of Terms

None.

# 19. List of Acronyms

AES - Atmospheric and Environment Service AFM - Airborne Fluxes and Meteorology

ASCII - American Standard Code for Information Interchange

BOREAS - BOReal Ecosystem-Atmosphere Study

BORIS - BOREAS Information System CD-ROM - Compact Disk-Read-Only Memory

CGR - Certified by Group CPI - Checked by PI

CPI-??? - CPI but questionable

DAAC - Distributed Active Archive Center

EOS - Earth Observing System

EOSDIS - EOS Data and Information System

F&P - Fisher & Porter

- Geographic Information System

GIS - Geographic Intormat.
GMT - Greenwich Mean Time

GSFC - Goddard Space Flight Center HTML - HyperText Markup Language IFC - Intensive Field Campaign

MARSII - Meteorological Automatic Reporting System II

MB - Manitoba

NAD83 - North American Datum of 1983

NASA - National Aeronautics and Space Administration

NSA - Northern Study Area

ORNL - Oak Ridge National Laboratory
PANP - Prince Albert National Park ΡI - Principal Investigator

PI - Principal I: PRE - Preliminary

READAC - Remote Environmental Automated Data Acquisition Concept

SK - Saskatchewan

SSA - Southern Study Area

T/RH - Temperature / Relative Humidity

TBRG - Tipping Bucket Rain Gauge URL - Uniform Resource Locator

#### 20. Document Information

#### 20.1 Document Revision Date

Written: 25-Jul-1995 Last Updated: 06-Jul-1999

#### 20.2 Document Review Date(s)

BORIS Review: 12-Jun-1998

Science Review:

#### 20.3 Document ID

#### 20.4 Citation

When using these data, please include the following acknowledgment as well as citations of relevant papers in Section 17.2:

These data were collected by the Atmospheric Environment Service of Environment Canada. The efforts of AES in providing these data are greatly appreciated.

If using data from the BOREAS CD-ROM series, also reference the data as:

Atkinson, G.B., "Environment Canada 15-Minute MARSII Data." In Collected Data of The Boreal Ecosystem-Atmosphere Study. Eds. J. Newcomer, D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers. CD-ROM. NASA, 2000.

#### Also, cite the BOREAS CD-ROM set as:

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM. NASA, 2000.

#### **20.5 Document Curator**

#### 20.6 Document URL

#### REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE September 2000	3. REPORT TYPE AND DATES COVERED Technical Memorandum		
4. TITLE AND SUBTITLE  Technical Report Series on the Bo  BOREAS AES MARSII Surf	oreal Ecosystem-Atmosphere	Study (BOREAS)	5. FUNDING NUMBERS  923	
6. AUTHOR(S) G. Barrie Atkinson and Barry Forrest G. Hall and David E.			RTOP: 923-462-33-01	
7. PERFORMING ORGANIZATION NAME Goddard Space Flight Center Greenbelt, Maryland 20771	E(S) AND ADDRESS (ES)		8. PEFORMING ORGANIZATION REPORT NUMBER  2000-03136-0	
9. SPONSORING / MONITORING AGE National Aeronautics and Space Washington, DC 20546-0001	• •	(ES)	10. SPONSORING / MONITORING AGENCY REPORT NUMBER  TM—2000–209891  Vol. 118	
11. SUPPLEMENTARY NOTES G.B. Atkinson and B. Funk: I Raytheon ITSS, NASA Godd		1 0		
12a. DISTRIBUTION / AVAILABILITY STA Unclassified—Unlimited Subject Category: 43		ormation	12b. DISTRIBUTION CODE	

#### 13. ABSTRACT (Maximum 200 words)

7121 Standard Drive, Hanover, MD 21076-1320. (301) 621-0390.

Canadian AES personnel collected several data sets related to surface and atmospheric meteorological conditions over the BOREAS region. This data set contains 15-minute meteorological data from six MARSII meteorology stations in the BOREAS region in Canada. Parameters include site, time, temperature, dewpoint, visibility, wind speed, wind gust, wind direction, two cloud groups, precipitation, and station pressure. Temporally, the data cover the period of May to September 1994. Geographically, the stations are spread across the provinces of Saskatchewan and Manitoba. The data are provided in tabular ASCII files, and are classified as AFM-Staff data.

BOREAS, aircraft flux meteorology, MARSII.			15. NUMBER OF PAGES 20 16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT $UL \\$